	тур	L #	Hit s	Search Text	DBs	Time Stam P	Comments	r D e f	E
1	IS& R	L45	149 6	(359/822,813,823).CCL S.	USPAT; US-PGPUB	2003 /11/ 18 13:0 8			0
2	BRS	L46	108 5	45 and (adjust\$4 or position\$4 or mov\$4)	USPAT; US-PGPUB	2003 /11/ 18 13:0 9			0
3	BRS	L47	64	45 and ((adjust\$4 or position\$4 or mov\$4) with ((cable\$1 or wir\$3) and spring\$3))	USPAT; US-PGPUB	2003 /11/ 18 13:1 5			0
4	BRS	L48	7	47 and knob\$1	USPAT; US-PGPUB	2003 /11/ 18 13:1			0
5	BRS	L49	53		USPAT; US-PGPUB	2003 /11/ 18 13:1			0
6	BRS	L50	27	49 and slid\$4	USPAT; US-PGPUB	2003 /11/ 18 13:1			0
7	BRS	L51	53		USPAT; US-PGPUB	2003 /11/ 18 13:1 7			0

	Тур	L#	Hit s	Search Text	DBs	Time Stam P	C o m m e n t s	e	Errors
1	BRS	L11		(adjust \$4 or	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:1			0
2	BRS	L12	930 2	11 and cable\$1 and spring\$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:1			0
3	BRS	L13	328 7	12 and ((carrier\$1 or support\$4) with optic\$4)		2003 /11/ 18 09:1 2			0
4	BRS	L14	361	13 and (slid\$4 near3 plate\$1)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:1			0
5	BRS	L15	269	13 and (x-axis)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:1 3			0
6	BRS	L16	281	13 and (y-axis)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2003 /11/ 18 09:1			0
7	BRS	L17	264 8	13 and (axis or axes)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
8	BRS	L18	264 8	15 or 16 or 17	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
9	BRS	L19	464	18 and bolt\$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0

	Туре	L #	Hit s	Search Text	DBs	Time Stam P	Comments	ErrorDefinition	s
10	BRS	L20	329	19 and ((adjust\$4 or position\$4 or mov\$4) near3 optic\$4)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
11	BRS	L21	16	20 and ((adjust\$4 or mov\$4 or position\$4) near3 (cable\$1 and spring\$1))	USPAT; US-PGPUB	2003 /11/ 18 09:5			0
12	BRS	L22	738	13 and ((y or x or z) near3 (axis or axes))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
13	BRS	L23	627	13 and ((y or x or z) adj2 (axis or axes))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
14	BRS	L24		15 or 16 or 17 or 23	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
15	BRS	L25	464	24 and bolt\$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0
16	BRS	L27		25 and ((adjust\$4 or mov\$4 or position\$4) near3 (cable\$1 and spring\$1))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003 /11/ 18 09:5			0